

## RAMEN 5C, 5D DEPARTURE [USN] SHL-2467 (ITAF)

DECIMOMANNU, ITALY

GND CON  
279.175  
DECIMOMANNU TOWER ★  
122.1 257.8  
CAGLIARI APP CON  
118.75 344.0


Rwy	Knots	60	120	180	240	300	360
*17 (a)	V/V(fpm)	300	600	900	1200	1500	1800
*35 (b)	V/V(fpm)	300	600	900	1200	1500	1800
†17 (c)	V/V(fpm)	250	500	750	1000	1250	1500
†35 (d)	V/V(fpm)	450	900	1350	1800	2250	2700

\* Minimum † ATC Climb Rate

- (a) to 5000  
(b) to 4000  
(c) 5000 to FL120  
(d) 4000 to FL120

NOTE: For MAX TAS 322 Knots, bank 30° or 2°/sec.  
For MAX TAS 280 Knots, bank 25° or 1.8°/sec.  
For MAX TAS 303 Knots, bank 28° or 1.93°/sec.  
For MAX TAS 252 Knots, bank 20° or 1.6°/sec.  
For MAX TAS 214 Knots, bank 15° or 1.36°/sec.

- ① 12.3 NM from Rwy 17  
② 22.6 NM from Rwy 35



EMERG SAFE ALT 100 NM 8200

TA 6000



## DEPARTURE ROUTE DESCRIPTION

**RAMEN 5D - TAKE-OFF RWY 17:** After take-off proceed on DEC R-168 to DEC 5 DME to be crossed at or above 1000, then left turn heading 322° to join DEC R-357 (track 357°) to RAMEN. Cross RAMEN at or above 9000.

**RAMEN 5C - TAKE-OFF RWY 35:** After take-off proceed on DEC R-348 to DEC 2 DME to be crossed at or above 1000, then turn right to join DEC R-357 (track 357°) to RAMEN. Cross RAMEN at or above 9000.

RAMEN 5C, 5D DEPARTURE

DECIMOMANNU, ITALY  
DECIMOMANNU (LIED)

Effective 3 AUG 2006 - 31 AUG 2006