

## RAMEN 5E DEPARTURE "CARGO JET/PROPELLER"

DECIMOMANNU, ITALY

GND CON  
279.175  
DECIMOMANNU TOWER ★  
122.1 257.8  
CAGLIARI APP CON  
118.75 344.0

[USN] SHL-2467 (ITAF)

Rwy	Knots	60	120	180	240	300	360
*17 (a) V/V(fpm)		250	500	750	1000	1250	1500
*35 (b) V/V(fpm)		300	600	900	1200	1500	1800
+17-35 (c) V/V(fpm)		400	800	1200	1600	2000	2400

\* Minimum † ATC Climb Rate

(a) to FL90

(b) to 4000

(c) to 5000

For take-off Rwy 17L  
use RAMEN 5D.

9000  
RAMEN  
L-12, H-15

① 2753 •


For MAX TAS 322 Knots, bank 30° or 2°/sec.  
For MAX TAS 280 Knots, bank 25° or 1.8°/sec.  
For MAX TAS 303 Knots, bank 28° or 1.93°/sec.  
For MAX TAS 252 Knots, bank 20° or 1.6°/sec.  
For MAX TAS 214 Knots, bank 15° or 1.36°/sec.

1000

②

DECIMOMANNU  
Chan 19 DEC

① 16.1 NM from Rwy 35



EMERG SAFE ALT 100 NM 8200

TA 6000

## DEPARTURE ROUTE DESCRIPTION

**TAKE-OFF RWY 35R:** After take-off proceed on DEC R-348 to DEC 2 DME to be crossed at or above 1000, then turn right heading 215° to join DEC R-168 (track 168°). At DEC 8 DME turn left to follow DEC R-132 (track 312°) to DEC, then right turn on DEC R-357 to RAMEN, cross RAMEN at or above 9000.

RAMEN 5E DEPARTURE "CARGO JET/PROPELLER"

DECIMOMANNU, ITALY  
DECIMOMANNU (LIED)

Effective 3 AUG 2006 - 31 AUG 2006