

Summary

0	Change notes	3
0.1	AIFIPIn v2.0 versus AIFIPIn v1.0	3
1	Introduction	5
2	References	5
3	AIFIPIn overview	6
4	Installation	10
4.1	New installation	10
4.2	Update from v1.0 to v2.n	10
5	AIFIPIn Settings window	11
6	Airports Selection window	12
6.1	Filtering panel	12
6.2	Selection of Destination Airports panel	13
6.3	AI Traffic Airports File sub-panel	13
6.4	Missing Airports list	14
7	Aircraft selection window	14
7.1	Flight Simulator Aircraft Database panel	14
7.2	Flight Plan Aircraft Models panel	15
8	Flight Planning – The main window	17
8.1	Main menu strip	17
8.2	General and display commands strip	19
8.3	Planning board description and legs representation	20
8.4	Flight Plans panel	21
8.5	Legs edition subpanel	26
8.6	Leg selection and scheduling by direct action of the cursor on the planning board	29

9	Timetable window	30
9.1	Airport textbox and Airport Change button	30
9.2	Timetable Traffic Source	30
9.3	Timetable sort keys	31
9.4	Other controls of the Timetable window	31
10	Airports Edition window	32
10.1	The AIFIPIn airports database	32
10.2	Airports Edition window and panels	33
10.3	The "Lists of Airports to be Edited" panel	33
10.4	The "Airport Edition" panel	34
11	Tutorial : Starting from scratch to create of a new flight plan	36
11.1	The flight plan to create	36
11.2	The preparation of the planning	37
11.3	The Flight Plan	39
12	AIFIPIn language translation	43
13	Legal aspects	44
13.1	Using AIFIPIn	44
13.2	Proposing AIFIPIn	44
13.3	Copyright information	44
14	Acknowledgements	44

0 Change notes

0.1 AIFIPIn v2.0 versus AIFIPIn v1.0

The main purpose of this second version of AIFIPIn is to introduce some new functions. The bases of the initial version of AIFIPIn are fully kept. Some minor corrections or complements have also been introduced.

- Filtering of the flight plans to be displayed on the planning board :
 - A new function (and its associated button) permits to automatically select the flightplans to be displayed on the planning board according to a preselected combination of 3 criteria: aircraft model, airport as a stopover of the flightplans and time when being on ground at the selected stopover.
 - A dedicated window permits to pre-define the combination of the filtering criteria to be applied and their values.
- Sort the flight plans list
 - The list of flight plans (defined as per the flightplans.txt file) can be sorted according to 3 sort keys among A/C model number, Registration, Traffic%, Repeat period and Flight rule. The selection of the sort keys is made via a dedicated window.
- Transfer of a set of legs in closed loop from a flight plan to another
 - This new function (and its associated button) permits to easily transfer a set of legs starting from one airport and coming back to the same airport (closed loop trip) from its original flight plan to another one. The targeted flight plan and its aircraft must be compatible with the transfer: initially on ground at the departure airport of the trip to transfer, during its complete duration, the targeted aircraft must also have a cruise ground speed of the same order of magnitude as the original aircraft.
- Timetable
 - A new function to build a timetable providing the list of all aircraft movements planned at a given airports. The timetable is sorted according to 4 sorting keys selected and ordered among the kind of movement (arrival or departure), the day, the hour, the airport, the city, the flight number, the aircraft type (i.e. aircraft model) and its registration.
 - A dedicated window permits to select the flightplans source files (in TTools format) to be also taken into account to establish the timetable.
- AIFIPIn Airports Database :
 - Airport editor : AIFIPIn v2.0 introduces an airport editor permitting to modify the parameters of airports or to add new airports in the airports database. The first time the editor is used to modify or create airports, a new airport database file, AIFIPInUserDB.txt, is added in the AIFIPIn base folder.
 - A new airports database file, AIFIPInUserDB.txt, is used. This new file is built on the same format as the basic file AIFIPInDB.txt but permits to record separately the airports modified or added by the user. AIFIPInUserDB.txt is not part of the AIFIPIn v2.0 distribution package ; it is automatically created when airports data are modified or new airports are created for the first time via the airports editor of AIFIPIn v2.0 (see above) .

- The airports database associated with AIFIPIn v1.0 was consisting in four different editable files linked the one to the others : AIFIPInDB.txt, AIFLPLNCitiesList.txt, ICAO Countries Code.txt and ICAO Wide Regions Code.txt. Both AIFLPLNCitiesList.txt and ICAO Countries Code.txt are not anymore used in the v2.0 version. The two remaining files, AIFIPInDB.txt and ICAO Wide Regions Code.txt are kept as they were in the initial version and are still necessary.
- Miscellaneous minor updates or corrections, including :
 - Brief information is provided as feedback when a source file (flightplan.txt, aircraft.txt, airport.txt or AIFIPInUserDB.txt) is created or updated.
 - Minimum stop time can be decreased down to 15 mn
 - Standard stop time : idem
- Files version configuration

File	AIFIPIn_v1.0	AIFIPIn_v2.0
AIFIPIn.exe	V1.0	V2.0
AIFIPIn.ini	N/A (automatic)	N/A (idem)
AIFIPInCustom_xx.txt	V1.0	V2.0
AIFIPInMsg_xx.txt	V1.0	V2.0
ICAO Wide Regions Code.txt	V1.0	V1.0
ICAO Countries Code.txt	V1.0	Canceled
AIFLPLNCitiesList.Txt	V1.0	Canceled
AIFLPLNDB.txt	V1.0 (or modified by the user)	V1.0 (or modified by the user)
AIFIPInUserDB.txt	Not existing	N/A (version not managed)
AIFIPInHelp_xx.pdf	V1.0	V2.0
Readme.txt	V1.0	V2.0
Miscellaneous	N/A	N/A

1 Introduction

"AIFIPIn" is simple manual edition tool of Flight Plans for Flight Simulator AI Traffic, according to AI Traffic standard conventions defined by the reference TTools of Lee Swordy for FS 2002 and FS 2004. The main objective of its design was simplicity and comfort of a user who wishes to create and edit manually AI Traffic Flight Plans.

The originality of AIFIPIn is mainly based upon the graphic representation of the edited Flight Plans on a planning board, providing by this way a visual understanding of the flight plan of one or several aircraft on a day or a week. Classical flightplan edition features such as scheduling in local time, day light saving, edition of the aircraft file content, etc, are also provided. AIFIPIn can be translated into any language based on the standard Roman alphabet.

AIFIPIn doesn't include any "compiler-decompiler" function. Its output is limited to the creation and/or the modification of the 3 files (Aircraft, Airports and Flightplans files) defined by Lee Swordy as the input files necessary to his well known compiler-Decompiler TTools (see [References](#) hereafter). Producing the AI Traffic .bgl file for FS9 or FSX goes through the use a compiler tool compatible with the reference standard input files format and conventions as defined by TTools.

It has to be noted that using AIFIPIn is at the own risk of its user!

2 References

Many "user-friendly", freeware programs have been created to manage AI flight plans and traffic and can be found on the web, each of them providing their own set of interesting and useful functions; some of them are mentioned hereafter:

- **TTools** by Lee Swordy: The Reference in the world of AI Traffic ; anybody interested in but not familiar with AI Traffic for FS has to read TTools manuals first. Furthermore, TTools is a "Compiler - De-Compiler" of AI traffic files for FS2002 and FS2004 ("FS9") and can be used to compile the files edited with AIFIPIn into a .bgl traffic files which can be read by FS9.
- **AITM** by Thomas Molitor : Includes several tools to manipulate the AI Traffic in many ways like rearrange, move, export, analyze, edition of flight plans and many others.
- **AI Flight Planner** by Don Grovestine : A multi-function tool for AI Traffic providing also a Compiler - Decompiler tool not only compatible with FS9 but also with FSX. Can use files formatted as per TTools Input files standard and thus should be adequate to compile AIFIPIn output files into FSX compatible traffic files.


3 AIFIPIn overview

Preliminary reminder about the basic concepts of AI traffic for Flight Simulator (FS9 / FS10) and the associated vocabulary :


An Aircraft of the AI Traffic is created as soon as a planning defining its operational flights and meeting certain rules is defined in an input file according to an adequate format for FS. This operational planning, called a **Flightplan**, is periodic (the repeat period being of 1 or several hours, up to 24 hours, or 1 week) and is made of successive flights called **Legs** joining the different stopovers of a closed loop trip. Each leg follows the great circle of the earth joining its departure stopover to its arrival stopover (nevertheless, the standard approach trajectories of FS are followed in principle)

Edition of flight plans with AIFIPIn goes through 3 different groups of commands or parameters, each of them being associated to a dedicated window :


- The main window is dedicated to the edition of the planning by itself, which consists in defining the characteristics of the base of the edited flights on one hand, and the characteristics of each leg of those flights on the other hand. Any flight can be drawn on the planning board offering a visual representation of its different legs. Scheduling of each leg (defining the departure time and the arrival time) can be done either via numeric up/down edition boxes, either directly by a drag and drop sequence on the planning board (a final adjustment via one of the numeric up/down edition boxes can be necessary to accurately set up the scheduled time).



- A second window is dedicated to the selection of the stopover airports to be used as destinations of the flight legs; those airports constitute the Airports file of the TTools convention.



- A third window is dedicated to the selection of the aircraft models upon which are based the aircraft the flights of which are planned. They constitute the Aircraft file of the TTools convention.



- A fourth window permits to get as a timetable the AI traffic planned at a given airport.

Nota : The planned traffic considered within the timetable is coming from user specified traffic source files formatted as defined by TTools convention.

The screenshot shows the 'AIFIPIn - Timetable' window. At the top, the 'Airport' is set to 'FKKD - Douala International'. Below this is a table of flight arrivals and departures. The table has columns for Arriv. or Dept., Day, Hour, From/To, City, Flight Nb, Aircraft, and Registr. The flights are listed for days 0, 1, and 2. To the right of the table is a 'Traffic Sources' panel with a 'Select' button and radio buttons for 'Currently edited traffic only', 'Other traffic files only', and 'Currently edited traffic and other traffic files'. Below that is a 'Sort Keys' panel with dropdown menus for Day, Arriv. or Dept., Hour, From/To, Flight Nb, Registr., Aircraft, and City, and a 'Sort' button. At the bottom right is a 'Traffic Density (%)' field set to 100.

Arriv. or Dept.	Day	Hour	From/To	City	Flight Nb	Aircraft	Registr.
A	0	05:15	LFPB - Paris Le Bourget	Paris	61	AI DC-8-50 Air Afrique	TU-TCB
A	0	11:05	FKKY - Yaoundé	Yaoundé	605	AI Caravelle Air Afrique	TU-TCY
A	0	11:15	FCBB - Maya-Maya	Brazzaville	62	AI DC-8-50 Air Afrique	TU-TCB
A	0	18:45	FKKY - Yaoundé	Yaoundé	607	AI Caravelle Air Afrique	TU-TCY
D	0	06:15	FCBB - Maya-Maya	Brazzaville	61	AI DC-8-50 Air Afrique	TU-TCB
D	0	08:45	FKKY - Yaoundé	Yaoundé	600	AI Caravelle Air Afrique	TU-TCY
D	0	12:15	LFPB - Paris Le Bourget	Paris	62	AI DC-8-50 Air Afrique	TU-TCB
D	0	13:00	FKKY - Yaoundé	Yaoundé	606	AI Caravelle Air Afrique	TU-TCY
A	1	04:30	DBBB - Cadjehou	Cotonou	159	AI DC-8-55F Air Afrique	TU-TCC
A	1	05:15	LFML - Marseille Provence	Marseille	87	AI DC-8-50 Air Afrique	TU-TCB
A	1	10:15	FOOL - Leon M'Ba International	Libreville	88	AI DC-8-50 Air Afrique	TU-TCB
A	1	10:35	FKKY - Yaoundé	Yaoundé	601	AI Caravelle Air Afrique	TU-TCY
A	1	14:35	FOOG - Port-Gentil	Port-Gentil	476	AI DC4 Air Afrique	TU-TBJ
A	1	14:50	FKKY - Yaoundé	Yaoundé	415	AI DC4 Air Afrique	TU-TCM
A	1	19:00	FKKY - Yaoundé	Yaoundé	409	AI DC4 Air Afrique	TU-TCM
D	1	06:15	FOOL - Leon M'Ba International	Libreville	87	AI DC-8-50 Air Afrique	TU-TCB
D	1	06:30	FTTJ - N'Djamena International	N'Djamena	184	AI DC-8-55F Air Afrique	TU-TCC
D	1	08:21	FOOL - Leon M'Ba International	Libreville	475	AI DC4 Air Afrique	TU-TBJ
D	1	08:45	FKKY - Yaoundé	Yaoundé	600	AI Caravelle Air Afrique	TU-TCY
D	1	11:15	LFML - Marseille Provence	Marseille	88	AI DC-8-50 Air Afrique	TU-TCB
D	1	13:00	FKKY - Yaoundé	Yaoundé	412	AI DC4 Air Afrique	TU-TBK
D	1	16:00	DNMM - Murtala Mohammed International	Ikeja, Lagos State	511	AI Caravelle Air Afrique	TU-TCY
D	1	16:15	FKKY - Yaoundé	Yaoundé	408	AI DC4 Air Afrique	TU-TCM
A	2	11:20	FKKY - Yaoundé	Yaoundé	403	AI DC4 Air Afrique	TU-TCM
A	2	13:10	DNMM - Murtala Mohammed International	Ikeja, Lagos State	510	AI Caravelle Air Afrique	TU-TCY
A	2	14:50	FKKY - Yaoundé	Yaoundé	413	AI DC4 Air Afrique	TU-TBK
A	2	19:00	FKKY - Yaoundé	Yaoundé	409	AI DC4 Air Afrique	TU-TCM

- A fifth windows is dedicated to the edition of airports data

The screenshot shows the 'Airports Edition' window. On the left is a 'Filtering panel' with 'World Region' checked and a list of regions including 'Africa & Indian Ocean'. Below it is a 'Country' list with 'Cameroon' selected. On the right is the 'Airports Edition' form. It has sections for 'Lists of Airports to be Edited' (with 'FKKO - Bertoua' selected), 'Airports only in Airports.txt File', and 'Missing Airports'. Below that is the 'Airport Edition' form for 'FKKO' (ICAO Code) and 'BTA' (IATA Code). The 'Country and City Edition' section shows 'World Region' as 'Africa & Indian Ocean', 'Country' as 'Cameroon', and 'City' as 'Bertoua'. At the bottom, the 'Airport Name' is 'Bertoua', 'Latitude' is 'N04° 32.99'', 'Longitude' is 'E013° 43.00'', 'Elevation' is '2133', and 'Time Zone (h)' is '1'.

- A sixth window is dedicated to the settings of AIFIPIn.



Any set of Aircraft, Airports and Flightplans files formatted as defined by TTools convention can be read as input data. The output of AIFIPIn is also consisting in those three files, also formatted as per TTools rules.

Several files are associated with the executable file AIFIPIn.exe and must be located in the same folder:

- AIFIPIn.ini keeps the settings parameters from the previous AIFIPIn session.
- The airports database associated with AIFIPIn, consisting in three different editable files linked the one to the others: AIFIPInDB.txt, ICAO Wide Regions Code.txt and AIFIPInUserDB.txt. The two first files must be present to allow AIFIPIn to run. The third one permits to record separately the airports modified or added by the user via the Airport editor of AIFIPIn v2.0. AIFIPInUserDB.txt is not part of the AIFIPIn v2.0 distribution package ; it is automatically created when airports data are modified or new airports are created for the first time via the airports editor. The airports selection can be done among the list of airports contained within this database which contains approximately 6800 airports ; they represent almost the totality of the airports recognized by the ICAO (International Civil Aeronautical Organization). It has to be noted that the Airports data-base of FS9 (and FSX) contains approximately 14000 airports; so the airports data-base of AIFIPIn is at the time being half of that size. Nevertheless this should not be a real problem in most of the cases. Should one or two airports be missing for the planning of a fleet of aircraft, it remains the possibility to add them with the airport editor of AIFIPIn V2.0.
- A set of customization files, AiFIPInCustom_xx.txt, AiFIPInMsg_xx.txt and AIFIPInHelp_xx.pdf. They permit to customize the menus and the command buttons of AIFIPIn for the first one, the information or warning messages for the second one and the current help file for the third. English (at least an approximation) and French versions (respectively _en and _fr suffixes) are provided at the time being.

4 Installation

4.1 New installation

To install AIFIPIn, unzip all the files contained into the compressed .zip distribution file into one folder of your choice (all the unzipped files must be located into the same folder.) AIFIPIn.exe can be run without any Windows program installation.

It may be requested to install some components of the Microsoft .NET Framework (version 2.0 or later). Nevertheless, tests performed on different computers and Windows XP (SP3) on which such components of the Microsoft .NET Framework had never been explicitly installed did not exhibit this requirement.

Compatibility mode with Windows XP (32 bits) programs may be requested if used with later version of Windows, especially Windows Vista - 64 bits or Windows 7 - 64 bits.

4.2 Update from v1.0 to v2.n

The simplest method to update AIFIPIn from v1.0 to v2.0 (or by principle from v1.0 to any further minor update v2.n) is to create a new folder dedicated to the new version and to unzip in it all the files contained into the compressed .zip distribution file of the new version, as for a new installation (see just above). This is enough to get the new version operative but some more work may be necessary:

- If you have created an Alias to activate AIFIPIn, don't forget to update it in order to activate the new AIFIPIn.exe.
- You may wish to recover the settings that you had selected for the previous version : Just copy the AIFIPIn.ini file from the original v1.0 version folder to the new v2.n folder.
- If the original AIFIPIn airports database from v1.0 have been modified by your own care :To recover your modified database in the v2.n version, just copy the AIFLPLNDB.txt file from the original v1.0 folder to the new v2.n folder, replacing the AIFLPLNDB.txt file extracted from the v2.n distribution package. Leave the ICAO Countries Code.txt and the AIFLPLNCitiesList.txt files in the original v1.0 folder since they are not anymore requested with v2.0 version of AIFIPIn.
- If you have created your own customization files (AIFIPInCustom_xx.txt and / or AIFIPInMsg_xx.txt) you have to perform some supplementary work to recover your customization in the new version :
 - Copy your own customized files from the original v1.0 version folder to the new folder, taking care to keep in the new folder both AIFIPInCustom_en.txt and / or AIFIPInMsg_en.txt
 - Using a simple .txt file text editor, copy the v2.0 section at the bottom of AIFIPInCustom_en.txt and / or AIFIPInMsg_en.txt into your own customized files (respectively AIFIPInCustom_xx.txt and / or AIFIPInMsg_xx.txt).
 - Proceed to the translation, line per line in the new copied section, of the text located on the right of each equal sign ("="). Don't alter the left part of any line, it would cancel the translation of the corresponding item or would suppress the corresponding message.
 - If not already done, copy the AIFIPIn.ini file from the original v1.0 version folder to the new v2.n folder, since the language code recognized by AIFIPIn is defined by the AIFIPIn.ini file (refer to the chapter [AIFIPIn language translation](#))

5 AIFIPIn Settings window

From the Flight Plans editing window, click on the "Settings" button or select the Settings option of the Tool Menu. The following window appears:




- Setting parameters :
 - Language (the default language is English) ; French is the unique alternative at the time being. Other languages should be available later.
 - Scheduled time resolution of 5 mn (checkbox) : If checked, the departure and arrival times are adjusted by steps of 5 mn, at the exception of the calculated arrival times (ETA) which keep a resolution of 1 minute. Checked by default.
 - Minimum stop time (minutes) : the lower limit of the duration of a stopover. A value of 45 mn or higher is recommended; however, in certain cases a lower value may be necessary but with the risk that aircraft don't land due to late arrival or not enough time available before departure time as scheduled. So the default value of the lower limit is set at 45 mn.
 - Standard stop time (minutes) : the stopover duration selected by default when a new leg is inserted in a flight planning. Default value set at 55 mn.
 - Minimum flight time (minutes) : the lower limit allowed for the duration of a leg. It is also the initial value for the duration of a new leg before its arrival airport is defined (initially, the arrival airport of a leg is identical to its departure airport). This parameter should not be set below the default value of 15 mn.
 - Daylight Savings Time (DST) activation (checkbox)
 - Daylight savings period (season from northern hemisphere) to be considered for DST, summer or winter

6 Airports Selection window

This window allows to create and/or to modify the list of Airports which are used as destinations of the edited flightplans (the content of the Airports File).

From the Flight Plans editing window, click on the "Airports" button or select the Airport Selection option of the Tool Menu. The following window appears:



6.1 Filtering panel

The filtering panel contains 3 filtering lists permitting to significantly facilitate the selection of airports by filtering the content of the drop-down list of the combo-box "ICAO Code – Airport Name" used for that selection.

- World Region: Each country belongs to one "World Region" (continental scale) according to its geographical location on the earth (with some exceptions, linked to the ICAO codification). One World Region being selected, the list of countries displayed within the country list-box is filtered or not according to the status checked or unchecked of the World Region checkbox. By the same way, the list of cities displayed within the City list-box is filtered or not, according to the status of both World Region and Country checkbox. Finally, the list of Airports displayed within the Airports selection combo-box (see Selection of Destination Airports) is filtered according to the same principle.
- Country: As above; each city belongs to a country.
- City: The same, for each airport.
- Command buttons:
 - ^ (up) : to change the position of the selected region in the list (one line, up)
 - v (down) : idem, down

- Sort : sort the list (alphabetic order)

6.2 Selection of Destination Airports panel

- ICAO Code – Airport Name: This combo-box permits to select airports to add or insert into the list of destinations airports.
- List of Destination Airports: The list of Airports which can be used within the edited flight plans. This list is the one contained within the airports file.
- Command buttons :
 - Insert -->: to insert the selected airport from the combo-box "ICAO Code – Airport" at the position of the one selected in the Destinations list (or in first position if no item is selected)
 - Add ---v : to add an airport at the bottom of the list
 - Remove : to remove an airports from the list
 - ^ (up) : to change the position of the selected item in the list (one position, up)
 - v (down) : idem, down
 - Sort : reorder the list of airports according to the rank of each airport World Region within the World Regions list, as a first sorting key; the alphabetic order of the ICAO code is the second sorting key. The interest of this sorting command is to group the Airports of a same World Region in a same area within the flights planning board; it has to be combined with the reordering functions dedicated to the World Regions list (see above).
 - Used : reduce the list to the airports used at least one time as a stopover within one of the edited flight plans. It has to be noted that using the complete set of available airports of the data base is not useful and slow down any scrolling of the planning board so much that it may become unacceptable for the user (airports file some time contains the totality of the Airports data base of FS : in such case, activating this "Used" function is highly recommended as soon as the Airport file is loaded).
 - OK : ends the destination airports selection and go back to the planning.

6.3 AI Traffic Airports File sub-panel

- Textbox : displays and permit to modify the current airports file associated to the Destinations Airports list
- Command buttons :
 - Add: add the content of the specified file (in the above text box) to the Destinations list. If one airport in the file is already within the list, it is ignored
 - Save: save the list of destination airports in the above specified file. If no file is specified, a save file dialog box asks for a file specification.
 - Save as: save the list of destination airports in a file specified by the user through a save file dialog box.


6.4 Missing Airports list

- List-box : Displays the list of airport ICAO codes called by the last loaded Flightplans file which have not been found neither within the corresponding Airports.txt file, neither within any of the airports data bases. See [The "Lists of Airports to be Edited" panel](#)

7 Aircraft selection window

This window allows to create and/or to modify the list of Aircraft models on which are based the edited flight plans (the content of the Aircraft File).

From the Flight Plans editing window, click on the "Aircraft" button or select the Aircraft Selection option of the Tool Menu. The following window appears:



7.1 Flight Simulator Aircraft Database panel

The Flight Simulator Aircraft panel permits to define the location of the Aircraft folder of Flight Simulator, to get the complete tree of the aircraft models variations available within this folder and to select aircraft models variation directly from that database. Any directory containing the same kind of files as the Aircraft directory of Flight Simulator (especially one subdirectory per aircraft model, containing each one "Aircraft.cfg" files) is suitable.

- Aircraft Directory textbox : Indicates which folder is selected
- Change button: Click on it to get a folder selection dialog box by which a new Flight Simulator Aircraft folder can be selected. The FS Aircraft Tree is then updated accordingly
- FS Aircraft Tree: Presents the complete aircraft models and variations available in the specified Aircraft folder. The aircraft tree is arranged according to 3 levels :
 - Level 1 : Aircraft Manufacturer level (ex : AI Douglas) – corresponds to the "UI_Manufacturer" parameter of the aircraft.cfg file
 - Level 2 : Aircraft Type level (ex : DC-8-50) – corresponds to the "UI_Type" parameter of the aircraft.cfg file

- Level 3 : Aircraft Variation level (ex : Air Afrique) – corresponds to the “UI_Variation” parameter of the aircraft.cfg file

Only selected items from Level 3 (aircraft variation) can be directly added or inserted in the list of Flight Plans aircraft models.

7.2 Flight Plan Aircraft Models panel

The Flight Plan Aircraft Models panel permits to edit the content of the Aircraft file.


- AI Traffic Aircraft File textbox : Indicates which Aircraft file is edited
- Aircraft models edition table :
 - AC# : The Aircraft number of the Aircraft file. Can be manually edited. Assigning to an aircraft a number already assigned to another aircraft is not allowed.
 - Cruise Ground Speed : 200 kts is given by default when a new aircraft is inserted or added and has to be manually adjusted to the correct value. Edited value must be within the range of 50 to 1500 kts.
 - Title (Aircraft File) : Corresponds to the “Title” parameter of the Aircraft.cfg file.
- Command buttons :
 - Load: load an existing aircraft file. This action is possible only if no flight plan is currently defined (see Flight Planning main window)
 - Save: save the list of aircraft models in the above specified file. If no file is specified, a save file dialog box asks for a file specification.
 - Save as: save the list of destination airports in a file specified by the user through a save file dialog box.
 - ReNum: Renumber the aircraft within the range of selected lines in the editing table, into a sequence starting at the number defined for the aircraft of the first selected line ; the step of the series is 1. If one aircraft number within the series is already affected to an aircraft outside the selected range, then the number is incremented until a “free” number is found (this is just to avoid to get several aircraft with a same number. This function is useful in particular for renumbering aircraft coming from FS2002 aircraft file or after modification of the order of the aircraft list
 - ^ (Up): to change the position of the selected item in the list (one position, up)
 - v (Down): idem, down
 - from FS Aircraft: When checked, the selected items of the FS Aircraft Tree (Level 3 - aircraft variation only) is directly added or inserted in the list of aircraft models when clicking on the Insert or the Add button ; the aircraft title is that defined in the Aircraft.cfg file for the selected variation. If unchecked, a tbd (to be defined) aircraft is inserted (or added) with the default ground speed of 200 kts. Then the Aircraft title has to be defined manually, as the ground speed.
 - Insert-->: Insert an aircraft just above the one selected in the editing table (or in first position if no item is selected). The number associated to the Aircraft is the smaller “free” (not already affected) integer starting from 1. A ground speed of 200 kts is given by default and has to be set to the correct value manually.
 - Add --v : The same as Insert but the new item is added at the bottom of the list

- Remove: To remove an aircraft from the list. An aircraft for which at least one flight plan has been defined cannot be removed
 - OK : Ends the aircraft models selection sequence and go back to the planning.
- Missing Aircraft: list of aircraft (AC# numbers) which have not been found in the Aircraft file associated to the last loaded Flightplans file. Those aircraft have to be inserted in the Aircraft file before reloading the Flightplan file. This list is empty in a normal situation.

8 Flight Planning – The main window

The main window of AIFIPIn is dedicated to the edition of the flight plans and is divided into 5 areas:

- The main menu strip
- The general and display commands strip
- The Flight Plans edition panel
- The Legs Edition sub-panel
- The Flight Planning board



8.1 Main menu strip

- File menu
 - New planning (Reset) : The same as the "Reset All" button of the Flight Plans edition panel. Erase all the current data, i.e. the airports list, the aircraft list and the flight plans in order to start a new planning from scratch.
 - Load a Flightplans file : The same as the "Load" button of the Flight Plans edition panel. Re-initialize the planning by loading the specified Flightplans file. If the associated Airports file and Aircraft file exist, they are loaded as well.

- Load (add) an Airports file : The same as the "Add" button of the [AI Traffic Airports File sub-panel](#). Add the content of the specified Airports file to the Destinations list. If one airport in the file is already within the list, it is ignored.
 - Load an Aircraft file : The same as the "Load" button of the [Flight Plan Aircraft Models panel](#). Load an existing aircraft file. This action is possible only if no flight plan is currently defined (see Flight Planning main window)
 - Save all three files : The same as the "Save all" button of the Flight Plans edition panel. Save the three AI traffic files, i.e. Airports, Aircraft and Flightplans files. If no Flightplans file has been previously specified, a save file dialog box asks for a Flightplans file specification.
 - Save the Flightplans file : The same as the "Save" button of the [Flight plans edition panel](#). Save the edited flight plans in the previously specified Flightplans file. If no file has been previously specified, a save file dialog box asks for a Flightplans file specification. If the airports list and/or the aircraft list have been modified since they have been loaded from or saved to their corresponding files, the user is prompted to know if these lists have to be saved or not.
 - Save the Airports file : The same as the "Save" button of the [AI Traffic Airports File sub-panel](#). Save the list of destination airports in the previously specified Airports file. If no file has been previously specified, a save file dialog box asks for a file specification.
 - Save the Aircraft file : The same as the "Save" button of the [Flight Plan Aircraft Models panel](#). Save the list of aircraft models in the previously specified Aircraft file. If no file has been previously specified, a save file dialog box asks for a file specification.
 - Save the Flightplans file as ... : The same as the "Save as" button of the [Flight plans edition panel](#). Save the edited flight plans in a file specified by the user through a save file dialog box. Then, if the airports list and/or the aircraft list have been modified since they have been loaded from or saved to their corresponding files, the user is prompted to know if these lists have to be saved or not.
 - Save the Airports file as ... : The same as the "Save as" button of the [AI Traffic Airports File sub-panel](#). Save the list of destination airports in a file specified by the user through a save file dialog box.
 - Save the Aircraft file as ... : The same as the "Save as" button of the [Flight Plan Aircraft Models panel](#). Save the list of destination aircraft models in a file specified by the user through a save file dialog box.
 - Exit : to exit from AIFIPIn
- Tools menu
 - Select Aircraft : The same as the "Aircraft" button of the general and display commands strip : call for the [Aircraft Selection window](#).
 - Select Destination airports : The same as the "Airports" button of the general and display commands strip : call for the [Airports Selection window](#).
 - Re-synchronize Legs numbering : The same as the "Re-Sync" button of the Flight Plans edition panel. Re-number the legs so that the legs number sequence is synchronized with the repeat period of the flight plan ; i.e. the leg from which the departure time is the first within the repeat period becomes the first leg of the flight plan.
 - Share traffic activation (%) thresholds : The same as the "Share %" button of the [Flight Plans edition panel](#). Randomly shares activation thresholds (%) values between the flight plans associated to each of the aircraft models. For a given aircraft model, the activation threshold values are determined according to the number of flight plans associated to that aircraft model, so that for this aircraft, the number of activated flight plans is consistent with the AI traffic density selected in FS. At least one flight plan associated with an aircraft

model is activated, getting an activation threshold of 1%. Example : let's assume that we have defined 3 flight plans for a given aircraft model (we have planned the flights of a fleet of 3 aircraft of the same type) ; we wish that if the traffic density in FS is set below 33%, only 1 of the flight plans is activated ; if it is set between 33% and 66%, then we expect to see 2 of the flight plans activated ; if it is set over 66%, then the 3 flight plans have to be activated. Then, for that aircraft model, the activation threshold values will be 1%, 33% (the real value is in fact rounded to 34%) and 66% ; those 3 values are randomly distributed to the 3 flight plans.


- Filtering keys to display the Flightplans : To display the subpanel allowing the selection of the filtering keys to display the flight plans. (See [Flight Plans panel](#))
 - Sort the Flightplans : To display the Sort flight plan subpanel which permits to sort the flight plans within the flight plan base edition table and to select and to order the sort keys to be applied. (See [Flight Plans panel](#))
 - Timetable : To call the [Timetable window](#)
 - Settings : The same as the "Settings" button of the general and display commands strip : call for the [AIFIPIn Settings window](#).
- Help menu : Call this help file

8.2 General and display commands strip

- General command buttons
 - Undo : Cancels the previous action applied on flight plans or on aircraft models. No limitation.
 - Redo : Redo the previously canceled actions
 - Airports : The same as the "Select Destination airports" item of the Tools menu : call for the [Airports Selection window](#).
 - Aircraft : The same as the "Select Aircraft" item of the Tools menu : call for the [Aircraft Selection window](#).
 - Settings : The same as the "Settings" item of the Tools menu : call for the [AIFIPIn Settings window](#).
- Displayed days commands
 - < (left) and > (right) buttons : Shift the first displayed day of the week on the planning by one day left (the day before) or one day right (the day after). By default the first displayed day of the planning is Sunday (day 0).
 - "1", "3" or "7" radio buttons : Select the number of days displayed on the planning.
- Displayed destinations
 - "All" and "Displ. Fl. Pln." Radio buttons : Select to display either all the airports contained within the complete list of destination airports or only the set of airports defined as stopovers of the currently displayed flight plans. This last mode permits in most of the cases to get all the stopovers of an edited flight plan visible on the screen without scrolling it, as illustrated below

A click on one of these buttons, even if they are already selected, permits to reset the scrolling of the board so that the first stopover of the currently edited flight becomes the first stopover to be displayed on the board.

- Time editing mode
 - GMT or Local Time radio buttons : select the mode of edition to schedule the time of departure and arrival of the currently edited leg within the leg edition sub-panel. It has to be noted that the time graduation displayed in the strip just above the planning always refers to GMT.



8.3 Planning board description and legs representation

The planning board is consisting in :

- The Time strip which contains a graduated time axis. 3 different time scales can be selected (see [Displayed days commands](#)) : 7 days, 3 days and 1 day.
- The column containing the displayed stopovers on the left side of the board; the stopovers are identified by their ICAO Code, the city where they sit and the name of the Airport.
- One line of the board is dedicated to each of the displayed airports (each one presenting series of 6 pm to 6 am (local sun time) shadowed area alternated with 6 am to 6 pm (idem) white area to help to visually differentiate day sun time from night sun time on the board at the considered airport). Those airport lines are separated by white lines on which are drawn the "flight segments" of the flight legs.
- Each leg of a flight plan is represented by 4 segments :
 - 1 – The departure segment, vertical and in a position aligned on the board consistently with the scheduled departure time
 - 2 – The flight segment, horizontal, representing the duration of the flight

- 3 – The arrival segment, vertical and joining the flight segment to the second horizontal segment which represents the ground phase of the leg, i.e. the stopover at the gate of the leg destination airport.
- 4 – The ground segment, drawn in the line of the board dedicated to the destination airport of the leg.

8.4 Flight Plans panel

- Flight Plans File (Textbox and buttons)
 - Flight Plans File textbox : Indicates which Flightplans file is currently edited
 - Load : Re-initialize the planning by loading the specified Flightplans file. If the associated Airports file and Aircraft file exist, they are loaded as well.
 - Save : Save the edited flight plans in the Flightplans file specified in the Flight Plans File textbox. If no file has been previously specified, a save file dialog box asks for a Flightplans file specification. If the airports list and/or the aircraft list have been modified since they have been loaded from or saved to their corresponding files, the user is prompted to know if these lists have to be saved or not.
 - Save All : Save the three AI traffic files, i.e. Airports, Aircraft and Flightplans files. If no Flightplans file has been previously specified, a save file dialog box asks for a Flightplans file specification.
 - Save as : Save the edited flight plans in a file specified by the user through a save file dialog box. Then, if the airports list and/or the aircraft list have been modified since they have been loaded from or saved to their corresponding files, the user is prompted to know if these lists have to be saved or not.
 - Erase all the current data, i.e. the airports list, the aircraft list and the flight plans in order to start a new planning from scratch. The corresponding files (from which the current data have been loaded) are not affected by this operation. If the airports list and/or the aircraft list and/or the flight plans have been modified since they have been loaded from or saved to their corresponding files, the user is prompted to confirm the reset action without saving the modified data.
- Flight plan base edition table (description per Columns)
 - AC# - Title : Defines the Aircraft model on which each flight plan is based. A dropdown list permits to select an aircraft model within the previously defined list of aircraft
 - Registr : Registration of the planned aircraft (any characters string, compatible with FS9 / FSX ATC convention for call signs if used)
 - % Column : Activation threshold of the flight plan ; must be within the range 1 to 99. A flight plan is activated if the FS9 (/ FSX to be confirmed) traffic density set for AI traffic is over this parameter. The default value is 1%.
 - Period: Repeat period of the flight. To be selected within values proposed by a dropdown list (Week, 24h, 12h, 8h, 4h, 2h, 1h)
 - Flight Rule : IFR or VFR (to be selected in a dropdown list)
 - Lgnd : Legend. The color of the Line representing the flight on the board. Not editable.
 - Draw (Check box) : If checked, the corresponding flight plan is displayed on the planning board.

Important note : Several or even all flight plans can be drawn at the same time on the planning board ; but only one of them can be edited at a given time, the one which is

selected (highlighted in blue) in the base edition table ; it is designed as the "currently edited flight plan" in this help document.

- Flight plan base command buttons

- Share % : The same as the option "Share traffic activation (%) thresholds" of the Tools menu. Randomly shares activation thresholds (%) values between the flight plans associated to each of the aircraft models. For a given aircraft model, the activation threshold values are determined according to the number of flight plans associated to that aircraft model, so that for this aircraft, the number of activated flight plans is consistent with the AI traffic density selected in FS. At least one flight plan associated with an aircraft model is activated, getting an activation threshold of 1%. Example : let's assume that we have defined 3 flight plans for a given aircraft model (we have planned the flights of a fleet of 3 aircraft of the same type) ; we wish that if the traffic density in FS is set below 33%, only 1 of the flight plans is activated ; if it is set between 33% and 66%, then we expect to see 2 of the flight plans activated ; if it is set over 66%, then the 3 flight plans have to be activated. Then, for that aircraft model, the activation threshold values will be 1%, 33% (the real value is in fact rounded to 34%) and 66% ; those 3 values are randomly distributed to the 3 flight plans.
- Insert --> : Inserts a new flight plan between the currently selected flight plan and the previous one in the flight plans edition table. The inserted flight plan inherits from its previous flight plan its aircraft model (AC#), its activation threshold (%), its repeat period and its flight rule. If the inserted flight plan is in first position within the edition table, these parameters take their default values : the aircraft model is the first of the defined aircraft models list, the activation threshold is 1%, the repeat period is 24 Hr and the flight rule is IFR. When a new flight plan is inserted, it contains two closed loop legs. Their departure and arrival airport is the first airport of the defined airports list. their departure time is set depending upon the initial repeat period, as follows :
 - Week : 1st leg departure set at day 0 (Sunday), 6:00 GMT and 2nd leg departure set at Day 6 (Saturday), 21:00 GMT.
 - 24 Hr : 1st leg departure set at 6:00 GMT and 2nd leg departure set at 21:00 GMT.
 - 12 Hr, 8 Hr, 4Hr and 2 Hr : 1st leg departure set at 0:00 GMT and 2nd leg departure set 60 mn before the end of the repeat period.
 - 1 Hr : 1st leg departure set at 0:00 GMT and 2nd leg departure set at 0:30 GMT. The choice of 1 Hr repeat period induces the probable necessity to reduce significantly the minimum stop time (cf Setting Parameters) and thus to take the risk of malfunction of the so planned Aircraft.

And their leg duration is the minimum flight duration; the flight level is set at FL 50.

Note : to be compiled into a FS9 traffic file, all the flight plans defined by a flightplans file (as output of AIFIPIn) must include at least **2** legs ; furthermore, each of the data fields (such as registration code of the aircraft, etc) must be completed.

- Add --v : Add a new flight plan to the list of flight plans in last position within the flight plans edition table. The same rules as above are applied to define the initial parameters of the added flight plan.
- Delete : Deletes the selected flight plan.
- ^ & v : Changes the position of the selected flight plan within the edition table, by one rank up or down.
- Re-Sync : Re-Synchronize the series legs of the selected flight plan with its repeat period, via a simple circular permutation, so that the first leg of the series is also the first one within the defined repeat period. This function is very useful at the end of the edition of a

complete flight plan, to be sure that the series of legs is correctly ordered with regard to the repeat period; it permits also to forget this requirement when inserting the legs in the flight plan during edition.

- Single : Uncheck the Draw checkbox of all flight plans of the edition table excepted that of the selected flight plan, so that only this flight plan remains drawn on the planning board.
- Filter : Check the Draw checkboxes of all flight plans of the edition table which meet the filtering criteria defined via the filtering keys to display the flight plans subpanel (see below), so that all these flight plans are drawn on the planning board. Pressing the Filter button when the filtering keys to display the flight plans subpanel is not displayed on the screen permits to get it displayed.
- Transfer : Transfer a set of legs starting from one airport and coming back to the same airport (closed loop trip) from its original flight plan to another one. Several conditions are requested to allow this function to operate :
 - Only the initial flight plan (containing the set of legs to be transferred) and the targeted flight plan have to be displayed; both are requested; the initial one must be the selected flight plan (highlighted in blue in the base edition table).
 - The set of legs to be transferred must correspond to a closed loop trip (starting from and coming back to the same airport).
 - The targeted flight plan and its aircraft must be compatible with the initial one:

The targeted aircraft must be on ground at the departure airport of the trip to transfer and during its complete duration; the minimum stop time condition must be verified before and after the closed loop trip to transfer.


The targeted aircraft must also have a cruise ground speed of the same order of magnitude (difference limited to 15% of the highest) as the initial aircraft.

To proceed to the transfer of a closed loop trip :

- Check the Draw checkboxes of both the initial flight plan and the target one; make sure that all other Draw checkboxes are unchecked.
 - Select the initial flight plan in the base edition table.
 - Select for edition the **first** leg of the trip to transfer either via the leg edition subpanel (Previous (<-) and following (->) leg selection buttons - see leg edition subpanel hereafter), either by direct selection of that leg on the planning board (click on one of the two vertical segments of the leg - see "Leg selection and scheduling by direct action of the cursor on the planning board", below).
 - Click on the Transfer button : if the conditions described above are met, the transfer is done and you can notice that the color of the legs of the transferred trip is now the color associated to the targeted flight plan.
- Subpanel for the selection of the filtering keys to display the flight plans :

This subpanel permits to define the criteria to be applied to the displayed flight plans filtering function described above (Filter button of the flight plans base). 3 filtering criteria, or key, can be defined, as described below.

Displaying this subpanel within the main window is obtained via the Tools menu of the main menu strip ("Filtering keys to display the flight plans" menu item) or by a click on the Filter button of the flight plans base.




- A/C model (text box) : defines an aircraft model as a filtering criteria; 2 ways can be used to set its value :
 - Using the "-->" button just at the left of the text box : the aircraft model of the currently selected flight plan in the flight plan base edition table becomes the A/C model criteria
 - Entering the A/C model number, with or without the prefix "AC#" : the corresponding aircraft model of becomes the A/C model criteria.
- A/C model setting button ("-->") : see just above
- A/C model checkbox : The A/C model criteria is activated as a filtering key when checked.
- Stopover (text box) : defines a given airport as a stopover to be a filtering criteria ; 2 ways can be used to set its value :
 - Using the "-->" button just at the left of the text box : the arrival airport of the currently edited leg of selected flight plan (the leg in edition in the legs edition subpanel) becomes the stopover criteria.
 - Entering the ICAO code of an airport : that airport becomes the stopover criteria
- Stopover setting button ("-->") : see just above
- Stopover checkbox : The Stopover criteria is activated as a filtering key when checked.
- Time at stopover adjustment (day, hour and minute up-down numeric edition boxes) : permit to define a time of presence on ground at the airport defined as stopover filtering key as a third filtering criteria.
- Time at stopover checkbox : activate the above time as a filtering key when checked ; the stopover criteria must also be defined and activated.

- Sort flight plan subpanel

This subpanel permits to sort the flight plans within the flight plan base edition table and to select and to order the sort keys to be applied. 3 sort keys among 5 column headers of the flight plan base edition table can be selected.

Displaying this subpanel within the main window is obtained via the Tools menu of the main menu strip ("Sort of the Flightplans" menu item).



- Up (^) and down (v) buttons : to increase or decrease the level of the selected item in the list of criteria. The 3 first items in that list are applied as flight plans sort keys.
- Sort button : to sort the flight plans within the flight plan base edition table.

8.5 Legs edition subpanel

This subpanel is dedicated to the edition of each leg of the currently edited flight plan. It permits to define all the parameters which characterize the legs, according to the rules of TTools (and finally FS9/FSX) for AI traffic flight legs description.

From top to bottom and left to right, we find :

- Selection of the leg to edit (<- button, -> button and selected leg text box)
 - Previous (<-) and following (->) leg selection buttons : to select the leg to edit among the different legs of the flight, by increment of one leg backward or forward. The leg selected for edition can be identified by its number displayed in the dedicated text box (see next item). On the planning board, the segments representing that selected leg (at the exception of the ground segment) are drawn with dotted lines. As a flight plan is periodic, the leg following the last leg of a flight plan is the first leg of that flight plan ; and the leg preceding the first one is the last one.
 - Leg number textbox : displays the rank of the leg selected for edition and the total number of legs defined in the edited flight plan.
- Insertion of a new leg (v-- button and --v button), deletion of a leg
 - v-- button : To insert a leg **just before** the selected leg. The new leg is inserted in the ground phase (A/C at the gate) of the previous leg, i.e. between the previous landing of the A/C and the departure of the selected leg ; it is just a closed loop flight landing at the same airport as its departure airport. The duration of that flight is equal to the minimum flight duration (standard value of 15 mn). The real destination of the new leg has to be adjusted as a second step via the "To" dropdown list (see hereafter). The departure time of the inserted leg is scheduled after the previous landing time plus a stop time either equals to the "standard stop time" parameter if enough time is available, either equals to the "minimum stop time" parameter. If the stop time where the new leg should be inserted is not long enough to meet the minimum stop time requirement (before and after the new leg flight phase), then the insertion is denied.
 - --v button : To insert a new leg in the ground phase of the edited leg. The same principles as above are applied. The departure time of the closed loop leg which is inserted is scheduled after the arrival time of the selected leg plus a stop time either equals to the standard stop time parameter or equals to the minimum stop time parameter according to the available time before the departure of the following leg. If the stop time where the new leg should be inserted is not long enough to meet the minimum stop time requirement (before and after the new leg flight phase), then the insertion is denied. It has also to be reminded that in a flight plan defined with a repeat period of less than 24 hrs, a leg cannot end after the end of the repeat period ; this rule is not applicable to flight plans with a repeat period of 1 week or 24 hrs ; in these cases, a leg starting before the end of the repeat period may end the day after.

- Delete button : To delete a leg. This action is equivalent to skip a stopover and directly join the departure airport of the deleted leg to arrival airport of the following one. The departure time remains that of the deleted leg. The arrival time is estimated according to the geographic situation of both the departure airport and the arrival airport. If the leg following the deleted one is a fly back to the departure airport of that deleted leg, then a closed loop leg is created and has to be deleted by a second click on the delete button. The last leg of a flight plan cannot be deleted.
- From and to Airports
 - From Airport textbox: Read only information of the departure Airport of the selected leg
 - To Airport textbox & combined dropdown list : Permits to change the destination of a leg by selection of an airport in the associated dropdown list. This list of selectable airport is the one defined in the [Airports Selection window](#). The modification of the destination of the selected leg also impacts the following leg since that airport is also its departure airport. Before the requested change is accepted, checking that enough time is available for both modified legs is performed ; if this condition is not fulfilled, the modification is denied (and an information message displayed). If the modification is accepted, a new arrival time at the new destination is calculated.
- Time display and scheduling
 - Departure and arrival time adjustment (day, hour and minute up-down numeric edition boxes) : To adjust the departure and the arrival time of the selected leg, only by click on the up or down arrows. The box dedicated to day selection is active only when the repeat period of the edited Flight is "WEEK" (cf Flight plan base edition table). The time displayed (and adjusted) is either GMT or Local Time according to the selected mode for time edition (cf Time editing mode in [General and display commands strip](#)). The resolution of the minute adjustment box is either 5 mn or 1 mn according to the status of the parameter "Scheduled time resolution of 5 mn" , checked or unchecked (Cf [AIFIPIn Settings window](#)).

Note : the arrival time adjusted in the corresponding up-down numeric boxes is active only if the status of the "fixed" arrival time checkbox is checked ; if not checked, the active arrival time is the calculated ETA (see below).

 - Local Time or GMT display boxes, departure and arrival: display the scheduled departure time and arrival time in the mode (Local time or GMT) opposite to the one selected for edition.
 - Leg ETE display textbox : Displays the calculated duration of the flight phase of the selected leg (ETE : "Estimated Time En route").
 - Calculated ETA (textbox and <- button) : Displays the time of arrival (ETA : "Estimated Time of Arrival") calculated as suggested by Lee Swordy (cf [References](#)) in his TTools manual; the flight phase duration is the sum of a fix 15 mn period covering taxiing and waiting time on ground plus the time necessary to fly over the portion of a great circle joining the departure to the arrival airports at the cruise ground speed of the aircraft defined in the aircraft models edition table (cf [Fligh Plan Aircraf Models panel](#)). The <- button permits to directly enter the calculated arrival time into the arrival time edition boxes. The time displayed in this textbox is either GMT or local time consistently with the time displayed in the arrival time edition boxes.
 - Fixed arrival time checkbox : Select for the edited leg which arrival time has to be considered : either the calculated one (checkbox unchecked) or the edited one in the edition boxes (checkbox checked). If the calculated arrival time mode is selected, the arrival time edition boxes can still be used, but without any check of the consistency of the edited time ; since no consistency check is performed when switching the arrival time mode from calculated to fixed, it is possible by this way to bypass all the checks which are normally performed and to select an inconsistent arrival time such as arrival before departure or after departure of the following leg or outside the repeat period etc. As it can be anticipated, in such a case, the resulting flight plan drawn on the planning board is not


consistent and the probability to get an AI Traffic aircraft following its flight plan in FS9/FSX is very poor. But in certain circumstances, this way may permit to recover abnormal situation that normal consistency checks do not permit to supersede.

- Touch and Go (TnG) checkbox : The role of this checkbox is comparable to that of the fixed arrival time one, but when checked, indicates that the A/C should perform touch and go when arriving at the destination airport of the leg until the edited arrival time is reached. Fixed and TnG checkboxes are exclusives the one with the other.
- Flight number, cruise flight level and call sign
 - Flight number textbox : must be filled by a string of numeric characters; initiated to 0 for the first leg of a flight and then to flight number of the previous leg for the following ones.
 - Cruise FL textbox : To define the Flight Level of the cruise phase of the selected leg. Initiated per default at a value depending upon :
 - 1 - the heading of the leg so that the standard FL attribution rule is respected at the best.
 - 2 - The cruise ground speed defined for the A/C model, according to the following principle :
 - > FL50 to FL100 for A/C ground speed less than 220 kts
 - > FL110 to FL280 for A/C ground speed in the range 220kts to 250 kts
 - > FL270 to FL360 for A/C ground speed in the range 250 to 400 kts
 - > FL310 to FL380 for A/C ground speed over 400 kts
 - > The initial FL of a new leg is proposed randomly within those ranges unless the calculated leg duration is not sufficient to reach that level according to the hypothesis that the climb and descent rates of an A/C with a ground speed less than 250 kts is 1200 ft/mn and those of an A/C with a ground speed over 250 kts is 2000 ft/mn ; in such a case, the proposed level is deduced from the calculated leg duration and the vertical speeds mentioned above.
 - Call Sign text box : Defines the ATC call sign mode ; must be either F (as flight number) or R (as registration). The default value is F.

8.6 Leg selection and scheduling by direct action of the cursor on the planning board

Selection and scheduling of a leg can be directly performed on the planning board via the mouse cursor.

- Leg selection : Put the cursor on one of the 3 flight segments of the leg to select and click on it (the cursor becomes black when it is positioned on one of the 3 flight segments of a leg which is still not selected). If the segment on which the cursor is set is the departure segment or the arrival segment (one of the two vertical segments of the leg representation), then the cursor takes the form of vertical bar and two horizontal arrows for horizontal adjustment (see figure below).



- Departure or arrival time adjustment : Click continuously on the departure or arrival segment to adjust and drag it up to the desired time. The time (in both system GMT and local time) corresponding to the cursor current position is displayed in the central square just at the left of the leg edition sub-panel. A final adjustment to the exact desired time may be necessary via the time edition boxes. If the arrival time mode selected for the edited leg is the calculated one, both departure and arrival are moved simultaneously since the leg duration is constant. Consistency checks are continuously performed during the drag operation so that the dragged segment stops to move when the limit of a scheduling rule (most of the time the minimum stop time rule) is reached.

9 Timetable window

This window permits to create a timetable of the AI traffic planned at a given airport and is obtain via the **"Timetable"** option of the **"Tool"** menu of the main menu strip

Arriv. or Dept.	Day	Hour	From/To	City	Flight Nb	Aircraft	Registr.
A	0	05:15	LFPB - Paris Le Bourget	Paris	61	AI DC-8-50 Air Afrique	TU-TCB
A	0	11:05	FKKY - Yaoundé	Yaoundé	605	AI Caravelle Air Afrique	TU-TCY
A	0	11:15	FCBB - Maya-Maya	Brazzaville	62	AI DC-8-50 Air Afrique	TU-TCB
A	0	18:45	FKKY - Yaoundé	Yaoundé	607	AI Caravelle Air Afrique	TU-TCY
D	0	06:15	FCBB - Maya-Maya	Brazzaville	61	AI DC-8-50 Air Afrique	TU-TCB
D	0	08:45	FKKY - Yaoundé	Yaoundé	600	AI Caravelle Air Afrique	TU-TCY
D	0	12:15	LFPB - Paris Le Bourget	Paris	62	AI DC-8-50 Air Afrique	TU-TCB
D	0	13:00	FKKY - Yaoundé	Yaoundé	606	AI Caravelle Air Afrique	TU-TCY
A	1	04:30	DBBB - Cadjehou	Cotonou	159	AI DC-8-55F Air Afrique	TU-TCC
A	1	05:15	LFML - Marseille Provence	Marseille	87	AI DC-8-50 Air Afrique	TU-TCB
A	1	10:15	FOOL - Leon M'Ba International	Libreville	88	AI DC-8-50 Air Afrique	TU-TCB
A	1	10:35	FKKY - Yaoundé	Yaoundé	601	AI Caravelle Air Afrique	TU-TCY
A	1	14:35	FOOG - Port-Gentil	Port-Gentil	476	AI DC-4 Air Afrique	TU-TBJ
A	1	14:50	FKKY - Yaoundé	Yaoundé	415	AI DC-4 Air Afrique	TU-TCM
A	1	19:00	FKKY - Yaoundé	Yaoundé	409	AI DC-4 Air Afrique	TU-TCM
D	1	06:15	FOOL - Leon M'Ba International	Libreville	87	AI DC-8-50 Air Afrique	TU-TCB
D	1	06:30	FTTJ - N'Djamena International	N'Djamena	184	AI DC-8-55F Air Afrique	TU-TCC
D	1	08:21	FOOL - Leon M'Ba International	Libreville	475	AI DC-4 Air Afrique	TU-TBJ
D	1	08:45	FKKY - Yaoundé	Yaoundé	600	AI Caravelle Air Afrique	TU-TCY
D	1	11:15	LFML - Marseille Provence	Marseille	88	AI DC-8-50 Air Afrique	TU-TCB
D	1	13:00	FKKY - Yaoundé	Yaoundé	412	AI DC-4 Air Afrique	TU-TBK
D	1	16:00	DNMM - Murtala Mohammed International	Ikeja, Lagos State	511	AI Caravelle Air Afrique	TU-TCY
D	1	16:15	FKKY - Yaoundé	Yaoundé	408	AI DC-4 Air Afrique	TU-TCM
A	2	11:20	FKKY - Yaoundé	Yaoundé	403	AI DC-4 Air Afrique	TU-TCM
A	2	13:10	DNMM - Murtala Mohammed International	Ikeja, Lagos State	510	AI Caravelle Air Afrique	TU-TCY
A	2	14:50	FKKY - Yaoundé	Yaoundé	413	AI DC-4 Air Afrique	TU-TBK
A	2	19:00	FKKY - Yaoundé	Yaoundé	409	AI DC-4 Air Afrique	TU-TCM

9.1 Airport textbox and Airport Change button


- Airport Textbox : Indicates the airport for which the timetable is established. To select an airport (or to change the airport), enter the ICAO code of that airport in the textbox, then press the return key.
- Change button : Call the window dedicated to the selection of the Stopover Airports ; this permits to use the "ICAO Code – Airport Name" combobox and the filtering subpanel (World Region, Country, City) to select the airport for which the timetable has to be established.

Press the OK button of the stopover selection window to come back to timetable window.

9.2 Timetable Traffic Source

The timetable is established on the basis of two different kind of traffic data : the traffic data currently in edition through AIFIPIn and the traffic data contained in traffic sources files formatted as per TTOOLS convention. The traffic files to be used can be selected via the Select Button as explained hereafter.

- Traffic Source radio buttons :
 - Currently edited traffic only : The time table is established exclusively on the basis of the traffic data currently in edition through AIFIPIn.
 - Other traffic files only : The time table is established exclusively on the basis of the selected sets of traffic files ; traffic data currently in edition is ignored
 - Currently edited traffic and other traffic files : both kind of traffic data are used to establish the timetable.
- Source button : Calls a Traffic Files Selection window permitting to select the traffic files (Flightplans*.txt) to be taken into account into the timetable. The traffic files are presented within a folder tree with checkboxes to be checked or unchecked. The root of the folder tree can be chosen (Change button of the Traffic files root folder subpanel)



9.3 Timetable sort keys

The timetable can be arranged according to 4 sort keys to select and to order among 8 different selectable criteria.

- " ^ " and " v " buttons : change the position of the selected item in the listbox of criteria to sort the timetable. The 4 top criteria are used as sort keys and are applied with the priority given by their rank in the listbox.
- Sort button : To sort the timetable according to the sort keys as defined by the criteria order in the listbox.

9.4 Other controls of the Timetable window

- Traffic Density numeric updown boxe : To select the traffic density (%) to be considered when establishing the timetable
- Print(.txt) button : print the timetable in a editable and printable .txt file. A save as dialog box permits to select a folder and the filename of the created timetable file.
- OK button : To close the Timetable window and come back to the main window of AIFIPIn.

10 Airports Edition window

This window permits to edit the parameters of existing airports of the AIFIPIn airports database or to define new airports. It is obtain via the "**Edit Airports**" option of the "**Tool**" menu of the main menu strip. Using the Airports Edition tool is probably the most "difficult" task to be performed with AIFIPIn and requests some attention at the first time.

10.1 The AIFIPIn airports database

The AIFIPIn airports data base is consisting in 2 different files, AIFIPInDB.txt and AIFIPInUserDB.txt. The first one contains the basic database of airports used by AIFIPIn and should not be anymore modified since the version v2.0 of AIFIPIn is available. The second file is build on the same format (see hereafter) as the first one but aims to record separately the airports modified or added by the user. When AIFIPIn is activated, the user database is loaded first, then the basic one; as AIFIPIn does not re-store an airport (identified by its unique ICAO code) already stored, only the user data of a modified airport are considered.

The format of AIFIPIn database is as follows :

- Each airport is described by one single record (one line of the file not starting by //)
- Each record must contain 10 fields (10 parameters) separated by semi-colons (";") :
 - ICAO code (4 digits, the 4th digit can be a blank character (" "))
 - Latitude (same format as within Airports File according to TTools convention)
 - Longitude (idem)
 - Altitude in feet
 - IATA code (3 digits, "." when undefined, can be just a null character (no character) but separators (";") must be present; not used yet by AIFIPIn.
 - Airport name
 - City
 - Country
 - Time shift (decimal hour; positive towards east)
 - DST (Daily-light Saving Time) system (1 letter according to the following code: E (Europe), A (US/Canada), S (South America), O (Australia), Z (New Zealand), N (None) or U (Unknown)).

10.2 Airports Edition window and panels

On a click on the **"Edit Airports"** option of the **"Tool"** menu of the main menu strip, the [Airports Selection window](#) is displayed first, then the Airports Edition window is displayed over the first one; only the Filtering Panel of the Airports Selection window is available, its others panels being deactivated (and normally hidden by the Airports Edition window).

The Airports Edition window comprises a first panel dedicated to different lists of airports and the Airport Edition panel properly said.

The role of the 3 filtering lists of the filtering panel is similar to their role in the Stopovers selection process, and permit to facilitate the selection of the airport to be edited.

The screenshot displays the 'Airports Edition' window, which is divided into two main sections. The left section, titled 'selection of the Stopover Airports', contains a 'Filtering panel' with three lists: 'World Region' (checked), 'Country' (checked), and 'City' (unchecked). The 'World Region' list includes 'Africa & Indian Ocean' (selected), 'America - Central, South & Caraïbean Island', 'America - North', 'Asia & Indonesian Islands', 'Australia, Pacific Ocean & Alaska', 'Europa - East, Meadle East & Asia Central', and 'Europa - West,North & Israel'. The 'Country' list includes 'Algeria', 'Angola', 'Ascension Islands', 'Benin', 'Botswana', 'Burkina Faso', 'Burundi', 'Cameroon' (selected), 'Canary Islands', and 'Cape Verde'. The 'City' list includes 'Bafoussam', 'Bamenda', 'Batouri', 'Bertoua' (selected), 'Douala', 'Dschang', 'Ebolowa', 'Foumban', 'Garoua', and 'Kribi'. The right section, titled 'Airports Edition', contains a 'Lists of Aiports to be Edited' panel with three lists: 'Airports from AIFIPIIn DataBase' (selected, showing 'FKKO - Bertoua'), 'Airports only in Airports.txt File', and 'Airports from AIFIPIIn User DataBase'. Below this is the 'Airport Edition' panel, which includes fields for 'ICAO Code' (FKKO), 'IATA Code' (BTA), 'World Region' (Africa & Indian Ocean), 'Country' (Cameroon), and 'City' (Bertoua). The 'Airport Name' field contains 'Bertoua'. The 'Latitude' field contains 'N04* 32.99'', 'Longitude' contains 'E013* 43.00'', 'Elevation' contains '2133', and 'Time Zone (h)' contains '1'. The 'DST Zone' dropdown is set to 'U - Unknown'. Buttons for 'Edit', 'Mod', 'Add', and 'Store' are visible throughout the interface.

10.3 The "Lists of Airports to be Edited" panel

This panel is dedicated to the selection of the airport to be edited and which can be selected within 4 combo-boxes, each one containing one particular list of airports.

- Airports from AIFIPIIn Database combo-box and associated Edit button: contains the list of airports of the basic airports database of AIFIPIIn, filtered according to the 3 filtering lists of the filtering panel and the status of the associated checkboxes. The Edit button permits to display the different parameters of the selected airport in the different textboxes of the Airport Edition panel and to edit them.
- Airports from AIFIPIIn User Database combo-box and associated Edit button: Similar to the previous one but containing the list of new or modified airports, corresponding to the user database. This list is also filtered by the filtering lists of the filtering panel. Any airport modified in the edition panel, then correctly stored, is transferred from its initial list to this list (although it may not be visible according to the filtering lists status.)

- Airports only in Airports.txt File combo-box and associated Edit button: This combobox contains the airports which have been loaded from an Airport.txt file but which have not been found in either the basic AIFIPIn airports database or the user one. In that case, only the ICAO code, the location and the altitude are defined and it may be useful to define the other parameters.
- Missing Airports combo-box and associated Edit button: Contains ICAO code of the airports mentioned within a loaded flight plan but not defined either within the corresponding Airports.txt file or within one of the airports database. The [Missing Airports list](#) is displayed also at the bottom of the Airports Selection window

Note : legs to or legs from such missing airports are simply ignored when AIFIPIn loads a flight plan; the best way to proceed in that circumstance is to create in AIFIPIn the missing airports by edition, store them, save the new/modified airports and then to reload the flight plan.

- Save button: Save all the newly defined or modified airports within the user database file (AIFIPInUserDB.txt).

Notes:

- **storing** (via the **Store button** of the Airport Edition panel) a new or modified airport adds it into the list of airports which can be used within AIFIPIn in the current session, but **do not save** that new or modified airport in the user database file.
- **If you wish to keep your new or modified airports in the user database file** (AIFIPInUserDB.txt), **don't forget** to click on **the Save button** after edition of them (at least before quitting the airport edition session, via the OK button.)
- OK button: to quit the airport edition session and come back to the main window.

10.4 The "Airport Edition" panel

- ICAO Code textbox: Contains the ICAO code of the airport in edition. To set the ICAO code to a new value, enter the code then press on the Enter key; a valid input (3 or 4 alphanumeric characters) is bolded and set to upper case ; an non valid input is replaced by the previous value. If the ICAO code corresponds to an airport already known within AIFIPIn, its parameters are displayed in the different textboxes of the edition panel.
- IATA Code textbox : Contains the IATA Code of the airport in edition. Must be 0 to 3 alphanumeric characters.
- Country and city edition group: Groups the textboxes dedicated to the definition of the location (World Region, Country and City) of the airport in edition and their associated buttons. They can be selected from each of the corresponding filters lists of the filtering panel by pressing the associated "Sel" Button just at the left of the textbox. The "Mod" and "Add" buttons on the right of the country and the city textboxes permit to respectively modify the name of the country or the city, or to create a new country or a new city in the location lists of AIFIPIn. The World Region cannot be edited.
 - Modification of the name of a country: Select the country to be modified in the country filtering list of the filtering panel. Press on the "Sel" button at the left of the country textbox; the initial name of the country is displayed in the country textbox; simultaneously, the World Region associated to that country appears in the dedicated textbox. Edit the name of the country in the country textbox; when you are satisfied with the new name, press the "Mod" button at the right of the country textbox. The new name of the country is now effective for all airports situated in this country; all these airports will be copied within the list of user modified airports and you will be invited to save that list in the Airports User Database file.
 - Creation of a new country: Select the world region where the new country is situated, then edit the name of the new country in the country textbox. Then press on the "Add" button at

the right of the country textbox. The new country is created in AIFIPIn, and you can now create cities in the new country or modify existing cities to get them located in the new country.

Note: to get the new country saved (via the Save button of the "Lists of Airports to be Edited" panel) within the Airports User Database, you need to define at least a city within your new country and to define at least one airport located in that city.

- Modification of the name of a city: This is exactly similar to the process of modification of the name of a country described above.
- Modification of the country in which the city is located : Select the modified country via the filtering list of countries and the "Sel" button associated to the country textbox. If that country does not exist in AIFIPIn, create it before as a new country (see above). Then press the "Mod" button at the right of the city textbox.
- Creation of a new city: Similar to the creation of a new country; start by the selection of the country in which the new city will be located. If that country does not exist in AIFIPIn, create it before as a new country (see above). Then edit the name of the city and press the "Add" button at the right of the city textbox.

Note : As for new country, to get the new city saved (via the Save button of the "Lists of Airports to be Edited" panel) within the Airports User Database, you need to define at least one airport located in that new city.

- Airport name textbox: Contains the name of the airport in edition.
- Latitude textbox: To set the latitude to a new value, edit it in the textbox then press on the Enter key. A copy/paste operation can be done, allowing a direct copy of the latitude of an airport location from a file or a web site for instance. Most commonly used format are accepted ("N" or "S", then decimal degrees, degrees and decimal minutes or degrees, minutes and decimal seconds); the format is automatically converted into the one compatible with that of the airport file according to TTools convention.
- Longitude textbox: Exactly similar to the latitude textbox.
- Elevation textbox : Altitude (referred to sea level) of the airport in edition, in feet.
- Time Zone textbox : Time zone of the airport in edition, in decimal hours, positive towards east.
- DST system combo-box: To select the DST (Daily-light Saving Time) system of the airport in edition.
- Store button: To store the airport in edition (either a modified airport or a new one) within the list of airports known by AIFIPIn. Any modification of the airport in edition is ineffective until it is stored via the store button.

Notes (reminder):

- **storing** (via the **Store button**) a new or modified airport adds it into the list of airports which can be used within AIFIPIn in the current session, but **do not save** that new or modified airport in the user database file.
- **If you wish to keep your new or modified airports in the user database file** (AIFIPInUserDB.txt), **don't forget** to click on **the Save button** after edition of them (at least before quitting the airport edition session, via the OK button.)

11 Tutorial : Starting from scratch to create of a new flight plan


11.1 The flight plan to create

To illustrate the way to proceed to create a new flight plan from scratch with AIFIPIn, let's choose to define the flight planning of the Caravelle F-BNRA from UTA in the middle of year 1968 ; she was flying in the Pacific area, joining Noumea (La Tontouta - NWWW) to Sydney (YSSY) twice a week and Noumea to Nandi (Fidji) (NFFN) once a week. UTA timetables from that period gives us the following time schedule :

- Tuesday (day2)
 - departure from Noumea to Sydney at 9:30 local time (GMT+11), flight ut2501, arrival at 11:50 local time (GMT+10)
 - departure from Sydney to Noumea at 13:10 local time (GMT+10), flight ut2502, arrival at 17:15 local time (GMT+11)
- Friday (day 5)
 - departure from Noumea to Nandi at 9:30 local time (GMT+11), flight ut2508, arrival at 12:35 local time (GMT+12)
 - departure from Nandi at 13:50 local time (GMT+12), flight ut2509, arrival at 15:00 local time (GMT+11)
- Saturday (day 6)
 - departure from Noumea to Sydney at 9:30 local time (GMT+11), flight ut2505, arrival at 11:50 local time (GMT+10)
 - departure from Sydney to Noumea at 13:10 local time (GMT+10), flight ut2506, arrival at 17:15 local time (GMT+11)


11.2 The preparation of the planning

- The Airports list
 - After activation of AIFIPIn, click on the Airports button to get the Airports selection window.
 - Then selection the world region Australia, Pacific Ocean & Alaska, and check on the World Region checkbox.
 - Selection of the Australia country, check on the Country check box, then selection of the city Sydney or directly the airport by its ICAO code YSSY if it is known, then click on the Add or the Insert button to insert that airport in the airport list.
 - Let's repeat the same process for La Tontouta (Noumea in New Caledonia - NWWW) and Nadi International (Nandi or Nadi in Fiji – NFFN), keeping this order. We should get something close to the following screenshot :



- Saving the Airports file (choose Airports_Tuto.txt as the file name) in the appropriate directory could be a good idea before quitting the session of airports selection by a click on the OK button.
- The Aircraft models list
 - The second thing to do before starting the planning is to define the list of aircraft models to be used. In our case, this list will be limited to one model. Let's click on the Aircraft button to get the Aircraft selection window.

- Let's assume that the model of our Caravelle UTA is still not defined anywhere in our PC; so it is not useful to load any FS Aircraft tree. As a consequence also, we have to uncheck the "from FS Aircraft" checkbox to be allowed to directly define a new aircraft model in the list.
- Let's click on the insert button : we should get something like the following screen shot, with a aircraft named "tbd" (as "to be defined") and a default ground speed of 200 kts.




- We have now to give a title to our (future) model and to correct its ground speed value; let's call it "AI Caravelle UTA" and give it a cruise ground speed of 360 kts as illustrated hereafter



- It remains now to save the list as Aircraft_Tuto.txt (to be consistent with the file name given to the Airports file) and to go back to the main window by clicking on the OK button.


11.3 The Flight Plan

- Initialization of the flight plan
 - We can now **create the flight plan** of our Caravelle by a click on the Insert or the Add button at the left of the flight plan base edition table. What we got should be like the following screen shot.




- We have then **to fill up or to correct the parameters of the base of the flight plan** in the edition table:
 - As there is only one model in the aircraft list, we got directly the right one in the first column "AC# -Title (Aircraft File)"
 - The registration of the aircraft is F-BNRA
 - We can keep the 1% activation threshold or change it to any value between 1% and 99%
 - The repeat period is the Week (to be selected in the associated drop-down list)
 - We keep the IFR flight rule


- The draw checkbox has to be checked to see the flight plan on the planning : it should consist in 2 closed loop legs of 15 mn each starting on Sunday from the first airport of our airports list, Sydney, the first one at 06:00 GMT and the second one at 21:00 GMT. Our screen should be now like the following one :



- We **shift the second leg up to the end of the repeat period** in order to be free to adjust the first leg where we want or to add all the new legs that we need. To do this we can select directly the second leg with the cursor (click left on one of the vertical segments of the second leg) and shift it to the right (like any drag and drop sequence). We get something close to the following screen shot :



- Since the first leg of the repeat period departs from an airport different from the first one in the airports list, we shall **fly the aircraft to the location where its first leg departs from by changing the destination of the second leg**, using the " to " combo-box of the legs edition subpanel. We should then get the following screen :



- Scheduling the Flight Plan

Scheduling the flight plan is now the easiest task ; we shall proceed as follows :

- Selection, then shift of the first leg up to its scheduled departure time; final adjustment of the departure time with the numeric edition boxes shall probably be necessary.
- The first leg destination is already the right one and don't need to be changed ; if it was not the case, we should modify the leg destination at that step.
- The arrival time has to be fixed at the scheduled one : We first enter the calculated ETA (should be day 2, 11:43 local time) into the arrival time edition boxes by using the "<-" button, then we do the adjustment to the scheduled time (day 2, 11:50 local time) ; it may be useful to check that the time shifts between local time and GMT are correct since there may be errors in the airports database (in several places in the world, the official time shift has been modified and the airport database may not reflect exactly the situation that we want to reproduce with our flight plan ; also, the daylight saving time may not be correctly set); finally we check on the fixed arrival time check-box.
- The flight number has to be set (2501).
- The flight level proposed is checked and may be corrected if not as we want. That's all for this leg.
- Insertion of the following leg by a click on the "--v" button ; a new leg (closed loop, 15 mn duration) is inserted departing 55 mn after the arrival of the first leg.
- Modification of the destination airport (flight back to Noumea).
- Adjustment of the departure time (day 2, 13:10 local time). Note : these 2 last steps could be done in the inverse order.
- Shift of the ETA into the fixed arrival time edition boxes ("<-" button) (note : if the 2 previous steps have been done in the inverse order as suggested, this is already done), then adjustment to the scheduled time (17:15) ; then we check on the fixed arrival time check-box

- Set up the flight number (2502) ; check the flight level.
- Repeat the same process for the next 3 legs (ut 2508, ut 2509 and ut 2505).
- We now have just to adjust the departure time and the arrival time of the last leg, to check on the fixed arrival time check-box and to set up the flight number (2506). That's all for our flight plan :

The screenshot shows the AIFIPIn software interface. The main window displays a table of flight plans with columns for AC#, Title, Registr., %, Period, Flight Rule, Lgnd, and Draw. The selected flight is AC#1 - Al Caravelle UTA, F-BNRA, 1 WEEK, IFR. The 'Legs Edition' panel on the right shows the flight details for flight 2506, including the origin (YSSY - Sydney International), destination (NWWW - La Tontouta International), departure time (06:13:10), and arrival time (06:17:23). The 'Fixed' checkbox is checked, indicating a fixed arrival time. Below the table, a flight path visualization shows the route from Sydney to Noumea and then to Nadi.

- The last thing to do is to save our work in Flightplans_Tuto.txt (Save or Save as).



17:10 local time, a Saturday evening, mid of august 1968; F-BNRA is landing at Noumea – La Tontouta, coming back from Sydney.

12 AIFIPIn language translation

AIFIPIn can be translated into any language based on the standard Roman alphabet. There is no particular difficulty, but just a little work to do so :

- First choose a language code in 2 letters (similar to "en" for English or "fr" for French) ; this code will be used as a suffix to the names of the customizable files corresponding to the new language
- Then copy the files AIFIPInCustom_en.txt, AIFIPInMsg_en.txt into the same folder (where AIFIPIn.exe is located), renaming them with the new suffix chosen just above, but keeping the root of their name as it is.
- Edit each of these new files with a simple text editor and perform the translation, line per line, of the text located on the right of each equal sign ("="). Don't alter the left part of any line, it would cancel the translation of the corresponding item or would suppress the corresponding message.
- Create a new help file in .pdf format and give it the name AIFIPInHelp_xx.pdf (where xx is your language code). Hopefully, this step is optional and can be done later ; in such a case, the original English version (this file) would remain the active help file.
- Edit AIFIPIn.ini with a simple text editor and complete the line starting by "LanguagesCodes =" (it should be the first effective line not starting with a comment mark "//") with a character string indicating first the new language, then the language code, respecting the syntax used to specify the language codes already defined.
- Check your work and perform the unavoidable adjustments which are necessary to get exactly what you want.

13 Legal aspects

13.1 Using AIFIPIn

AIFIPIn has been created by Bruno Thoraval in the context of a personal hobby, without any kind of professionalism especially in matter of software development. It is reminded that **using AIFIPIn or any part of it is at the own risk of its user !**

13.2 Proposing AIFIPIn

AIFIPIn is freeware and can be proposed to the members of the flight simmers community who may find some interest in using it as far it is proposed to them for **free** and exclusively in a form containing **exactly** the content of a distribution package prepared by its author for that purpose; redistributing such a distribution package with any file added, removed or modified is prohibited. The inclusion of any individual file from such a distribution package in another distribution archive without the prior permission of the AIFIPIn's author is prohibited. **Commercial usage of AIFIPIn in part or in totality is also prohibited** except express written permission of AIFIPIn's author.

13.3 Copyright information

Microsoft, Microsoft Windows and Microsoft Flight Simulator are trademarks of Microsoft Corp.

14 Acknowledgements

Many thanks to :

Lee Swordy for his fundamental tool "TTools" and the associated manual which permits to discover the bases of the AI Traffic world.

Thomas Molitor for his tool "AITM" and the powerful functions that it proposes to manipulate AI Traffic data.

Don Grovestine for his AI Flight Planner and his analyses of the AI Traffic behavior.

John Allard, from the Ocala Flight Sim Club and also active member of the Mutley's Hangar forums, for his encouraging comments and recommandations about AIFIPIn.